














LED Canopy Luminaire, 180W, 120-277V, DLC Listed

SKU #	VGHB28064S150V27	
Product Name	Canopy, Gas Station surface mounted LED Luminaire	
Description	LED Canopy Light, 180W, 120-277VAC	
Watts (W)	181.1	
Output Current at 120VAC	700mA	
Light Output (Lumens)	16401	
Efficacy (Lumens/Watt)	90	
Color Accuracy (CRI)	74	
Color Temperature (K)	Day White- 5119K	
Lighting Angle/ Lens Type	Type I (S1S)	
Power Factor	>0.9	
Working Voltage	100-277VAC	
LED Count / Type	84 / CREE XP-G LEDs	
Lens Reflector Style	Clear	
Operating Temperature (°F)	-40F to 131F (-40C to 55C)	
Mount/Base Type	Surface Mounted (4)	
Dimensions in inches (mm)	19.2"x13"x6.7"- 488mm*330mm*130mm	
Weight in pounds (kg)	22.13 lbs- 10.06 kg	
Body Color Choice	Silver Grey, Black, Brown, White	
Typical Life Expectancy -L70 Hours	>50000	
Approvals / Certifications	DLC, UL	
Photometric Data Available?	IES File	
Humidity Protection	10% to 95% IP65	
Total Harmonic Distortion	THD<20%	
Warranty	5 years	 <p>Luminous Intensity Unit : cd/klm</p>

Features:

Power Saving:	At least 60% Energy Saving,
Long life:	LEDs last longer than 50,000 hrs (at 12 hrs/day about 10 years)
Heat Dissipation:	Patented heat dissipation design achieves optimum efficiency
Modular Design:	Modules can be replaced for another kind of application
Installation:	Single bracket design which can be used for manifold installation requirement
Lab Tested:	Lab tests according to IES Standards
Solid-State:	High-Shock and High-Vibration Resistant
Instant-On:	Light turns on right away, without delay on Re-Stricke
High CRI:	High CRI enhances all original colors
Application:	Warehouse, Canopy, Highbay/Lowbay, Gas Station, Gym, Sports Facility

Lamp Series	Power Consumption of one module (W)	Module Qty	Mounting Method	Lens Type	Color Temperature	Input Voltage (120-277VAC)
VGHB	28	06	4	S1	50	V27

Comments:

Note: All specifications are subject to change without notice. Contact your distributor or e-mail: info@valuegreen.com for the latest specifications.

ValueGreen, Inc. 21354 Nordhoff St. Suite 108, Chatsworth, CA 91311, USA www.valuegreen.com

888-874-5664, 818-998-7008, Fax: 818-998-7042, info@valuegreen.com